

## Product data sheet uvex 1 x-tended support 6568.1-.3 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

|                            |   |
|----------------------------|---|
| <b>General features</b>    | <ul style="list-style-type: none"><li>• Sporty, multifunctional safety shoe</li><li>• Especially lightweight and flexible</li><li>• Breathable, perforated high-tech micro velour upper material</li><li>• Foamed polyurethane scuffcap helps increase product life of upper</li><li>• Suitable for people allergic to chrome. Made from synthetic materials</li><li>• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances</li><li>• BOA® Fit System for a fast, effortless, precision fit</li></ul>                             |
| <b>Protection features</b> | <ul style="list-style-type: none"><li>• 100% metal-free uvex xenova® toe cap - compact design, anatomical shape, good lateral stability, no thermal conductivity properties</li><li>• Metal-free, penetration-resistant insole in accordance with the latest standard, which does not impact shoe flexibility</li><li>• Medial and lateral heel support for the foot through an especially designed side frame to protect against ankle injuries, for guidance and impact protection</li><li>• Meets the ESD specification with volume resistance less than 35 megaohms</li></ul> |
| <b>Comfort features</b>    | <ul style="list-style-type: none"><li>• Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials</li><li>• Virtually seamless design to eliminate pressure</li></ul>  |

|                             |  |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
|-----------------------------|--|----------|--------|----|----|-------|----|----|----|----------|----------------------------|--|--|------|---------|--|--|
|                             | <p>points</p> <ul style="list-style-type: none"> <li>• Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot</li> <li>• Distance mesh lining provides optimum breathability</li> <li>• Soft padded collar and tongue</li> </ul>  |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| <b>Outsole</b>              | <ul style="list-style-type: none"> <li>• PUR outsole, non-marking</li> <li>• Ergonomically designed tread</li> <li>• Multi-layer-shock absorption system using dual density polyurethane for walking comfort</li> <li>• Excellent slip resistance</li> <li>• Self-cleaning tread</li> <li>• Resistant to oil and petrol</li> </ul>   |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| <b>Certificates</b>         | <ul style="list-style-type: none"> <li>• Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.</li> </ul>  |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| <b>Areas of application</b> | <ul style="list-style-type: none"> <li>• Light applications</li> </ul>   |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| <b>Technical data</b>       | <table> <tr> <td>Art.-no.</td> <td>6568.1</td> <td>.2</td> <td>.3</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> </tr> <tr> <td>Standard</td> <td colspan="3">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Size</td> <td colspan="3">35 – 52</td> </tr> </table>   | Art.-no. | 6568.1 | .2 | .3 | Width | 10 | 11 | 12 | Standard | EN ISO 20345:2011 S1 P SRC |  |  | Size | 35 – 52 |  |  |
| Art.-no.                    | 6568.1   | .2       | .3     |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| Width                       | 10   | 11       | 12     |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| Standard                    | EN ISO 20345:2011 S1 P SRC   |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| Size                        | 35 – 52  |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |
| <b>Accessories</b>          | <p><i>uvex 1 comfortable climatic insole</i><br/>(article no.: 9534.7-9)</p> <ul style="list-style-type: none"> <li>• Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li> <li>• Ultra breathable and moisture-absorbing materials</li> <li>• Shock absorption zones that assist natural movement</li> <li>• Non-irritating, comfortable surface structure</li> </ul> |          |        |    |    |       |    |    |    |          |                            |  |  |      |         |  |  |