

Product Datasheet model uvex x-fit 9199 280



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

1. Product Characteristics

- classic, close fitting safety spectacle with extension kit options
- frameless lens design for a wide field of vision
- adjustment for every head and facial shape with the optional uvex Comfort Slider - a multi-stage temple inclination that allows wearers to achieve their own comfortable wearing position
- modular system allows functional accessories to be attached enhancing the ability to get on with the job
- nose bridge designed for all-day comfort
- robust polycarbonate lens with uvex's proven supravision coating technology – permanent anti-fog and scratch-resistant lens
- UV400 100 % protection against dangerous UVA and UVB radiation up to 400 nm
- optional clip-in frame seal provides extra protection against particles, dirt and dust
- metal-free

2. Technical Details Body		
Side arms		
Material	ABS	
Colour	grey translucent	
Marking		
Manufacturer's ID code	W	
Applicable EN norm	166	
Impact resistance	F (45 m/s)	
Resistance to high speed particles at extremes of temperature	Т	
Conformity symbol	CE	

3. Technical Details Lens		
Material	PC	
Thickness	1.9 mm at PD	
Coating	uvex supravision excellence	
Colour	grey 23%	
UV protection	UV400	
Marking		
Filter	5-2.5 (EN 172)	
Manufacturer's ID code	W	
Optical class	1	
Impact resistance	F (45 m/s)	
Resistance to high speed particles at extremes of temperature	Т	
Scratch resistance	К	
Antifog	Ν	
Conformity symbol	CE	
Factory symbol		

4. Logistical Information					
Product					
Weight	23g				
Dimensions (L x W x H) in approx. mm	Länge // Length Tiefe // Depth	HQte // Heli	picture only for reference		
	155 x 142 x 46				
	Packing unit 1	Packing unit 2	Packing unit 3		
EAN Code	4031101675640	4031101675640	4031101675640		
Quantity in pcs.	1	10	160		
Dimensions (L x W x H) in approx. mm	Lange Depth	Hotel Height	Arene Hours		
	65 x 155 x 58	185 x 290 x 97	600 x 400 x 400		
Net weight in approx. g	23	230	3,680		
Gross weight in approx. g	37	475	8,480		
Country of Origin	Germany				

5. Miscellaneous		
Standards	EN 166 + EN 172	
PPE Category	Category II	